

MIAx Pearl Options Exchange

Options FIX Drop using FIX Protocol FIX Drop Specification

Revision Date: 07/25/2023

Version 1.1c

© 2023 Miami International Holdings, Inc., and its subsidiaries. All Rights Reserved.

Proprietary Information of Miami International Holdings, Inc., and its subsidiaries.

Table of Contents

| | |
|--|-----------|
| 1. Overview | 1 |
| 1.1 Exchange Related Information | 1 |
| 1.2 Certification for the FIX Drop | 1 |
| 1.3 FAQs | 2 |
| 1.4 Configuration | 2 |
| 2. FIX Message Format and Delivery | 4 |
| 2.1 Standard Message Header | 4 |
| 2.2 Standard Message Trailer | 7 |
| 3. Session Protocol | 8 |
| 4. Administrative Messages | 9 |
| 4.1 Logon Request (MsgType = A) | 9 |
| 4.2 Heartbeat (MsgType = 0) | 9 |
| 4.3 Test Request (MsgType = 1) | 10 |
| 4.4 Resend Request (MsgType = 2) | 10 |
| 4.5 Reject – Session Level (MsgType = 3) | 11 |
| 4.6 Sequence Reset (MsgType = 4) | 12 |
| 4.7 Logout Request (MsgType = 5) | 12 |
| 5. Application Messages | 13 |
| 5.1 Execution Report (MsgType = 8) | 13 |
| 5.2 Trade Cancel/Correct (MsgType = UCC) | 17 |
| 6. Business Reject (MsgType = j) | 21 |
| Appendix A: Additional Billing Parameters | 22 |
| Appendix B: Contact List | 24 |
| Appendix C: Revision History | 25 |

1. Overview

The MIAX Pearl FIX Drop (FXD) is a messaging interface that provides real-time trade information corresponding to a firm's orders.

FXD uses FIX protocol version 4.2 (with minor customization) for both application messages and session level messages. For detailed information regarding FIX protocol and session protocol, please refer to the FIX documentation provided by FIX Protocol Limited (FPL) on their website <http://www.fixprotocol.org>.

This specification is intended to only be used by MIAX Pearl member firms and the firms that are sponsored for MIAX Pearl access by Pearl member firms. MIAX Pearl is referred to as Pearl for the rest of this document.

1.1 Exchange Related Information

1.1.1 Hours of Operation for Pearl Options Exchange

Please refer to MIAX website at <http://www.MIAXGlobal.com> for details about times for each of these events.

Note: Times specified below are as per timings of United States Eastern Time zone.

| | |
|---------------------------|--|
| 7:30 am | Firm Interface Start up time Firms are allowed to connect |
| 9:30 am to 4:00 pm | Trading Session for Equity Options (ends at 1:00 pm on early closing days) Note that Pearl may still send queued executions even after the end of this time range |
| 9:30 am to 4:15 pm | Trading Session for ETF and Index Options (ends at 1:15 pm on early closing days) Note that Pearl may still send queued executions even after the end of this time range |
| 5 pm (approx.) | End of Session (ends at 2 pm on early closing days) FIX Drop has completed sending all messages and Firms will soon be disconnected |

Firms are expected to stay connected at least until End of Order Cancel Acceptance because system can send executions and cancels due to production closing logic. Disconnecting before that can result in not receiving key information about order status changes.

1.1.2 Obtaining More Information

Information such as (but not limited to) membership, rules, fees and support can be obtained by sending an email to Trading Operations or by visiting MIAX website at <http://www.MIAXGlobal.com>.

1.2 Certification for the FIX Drop

Pearl will provide a test area for member firm's testing and certification needs. Please contact MIAX Trading Operations to obtain more information about this environment.

In order to connect to Pearl production, member firms must certify their application with Pearl. This certification testing is a manual process. In order to schedule a certification test, please email MIAX Trading Operations.

1.3 FAQs

Executions/Busts/Adjustments: All partially filled, filled executions, trade cancels (busts) and corrections (adjustments) are conveyed to firms via FIX Drop. Order acknowledges, rejects, cancels and replaces are not conveyed to firms via FIX Drop.

Multiple FXDs: In the event a firm needs multiple FXDs sending executions for the same MPIDs, the order of executions received on one FXD can be different than that of another FXD. Firms are recommended to arbitrate using execution report information and not FIX sequence numbers.

Failure/Recovery: In the event of a catastrophic hardware problem servicing FIX Drop, Pearl will activate backup FIX Drop services on alternative hardware with different IP addresses. Other than a change in IP address, the FIX session can be reestablished just as after a normal disconnect and resynchronized per normal FIX protocol. Note that selected outbound messages, from Pearl to the Firm, in transition during the failure, may be sent **or resent** with PossResend=Y. Firms may have already seen some of these messages before, with lower sequence numbers, and should handle the possible duplicate communications

Note that the backup FIX Drop Copies are not available for connectivity testing during the trading day.

Firms are encouraged to conduct failover testing to ensure seamless interaction during such events.

1.4 Configuration

Firms can configure their session(s) with the below properties.

Comp ID: All messages sent in either direction must contain SenderCompID and TargetCompID. Firms and Pearl will agree upon the values, to be used for these fields, at the time of initial setup. Firms are allowed to use a single Comp ID for each connection. Pearl will allow connections from a preconfigured computer (CompID).

Firm to Pearl

| SenderCompID | TargetCompID |
|--------------|--------------|
| Firm Comp ID | Pearl |

Pearl to Firm

| SenderCompID | TargetCompID |
|--------------|--------------|
| Pearl | Firm Comp ID |

TargetSubID: The TargetSubID in the execution reports contain the SenderSubID from a firm's order entry.

IP Address: At the time of setup, Pearl will require Firms source IPs and will allocate one or more Pearl FIX Drop server IPs to your firm as agreed upon by the Firm and Pearl membership.

Port: At the time of setup, Pearl will allocate one or more Pearl FIX Drop server ports as agreed upon by the Firm and Pearl membership.

Configuration: A FXD can be set up to send messages of one or more MPIDs belonging to the same member firm. For example, a firm has a MM division that use MPID A on one FIX Order Interface (FOI) and an EEM/OFP division

that uses MPID B and MPID C on three other FOIs, a FXD can be set up to send executions for MPID B and MPID C only (note that this excludes executions for MPID A).

2. FIX Message Format and Delivery

Please refer to **FIX v4.2 Protocol** document (<http://fixprotocol.org/specifications>) for details about **FIX message format and delivery**. That section offers insights into the general format of a FIX message being comprised of a standard header followed by the message body fields and terminated with a standard trailer. It further states that the non-printing, ASCII “SOH” (#001, hex:0x01, referred to in this document as <SOH>) must be used as the field and message delimiter.

FIX Drop will accept FIX session administrative messages from the firm. Any application message sent to the FIX Drop will result in a business reject back to the firm.

Data Types:

Price field formats are specified in the messages

Char String fields are case sensitive unless otherwise noted

2.1 Standard Message Header

The Standard Header precedes each administrative or application message in the FIX protocol. The header identifies the message type, length, destination, sequence number, origination point, and time.

The following table contains the Standard Header tags processed by Pearl. Any other header tag will be ignored.

| Tag | FIX Name | Req'd | Details |
|-----|-------------|-------|--|
| 8 | BeginString | Yes | Always the first field in a FIX message. Valid value: FIX.4.2 |
| 9 | BodyLength | Yes | Always the second field in a FIX message. Length of message expressed as the number of characters in the message following the BodyLength field up to, and including, the delimiter immediately preceding the CheckSum tag (“10=”). |

| Tag | FIX Name | Req'd | Details |
|-----|--------------|-------|---|
| 35 | MsgType | Yes | <p>Always the third field in a FIX message.</p> <p>Defines the message type.</p> <p>Valid values - Administrative messages: '0' = Heartbeat '1' = Test Request '2' = Resend Request '3' = Reject (Session level reject) '4' = Sequence Reset '5' = Logout 'A' = Logon</p> <p>Valid values – Application messages: '8' = Execution Report 'j' = Reject (Business message reject) 'UCC' = Trade Cancels and Corrections</p> |
| 34 | MsgSeqNum | Yes | Message sequence number (numeric). |
| 43 | PossDupFlag | No | Ignored |
| 49 | SenderCompID | Yes | <p>Identifies the party sending the message.</p> <p>The sending firm should use their Line Identifier as assigned by Pearl.</p> <p>Pearl will use “Pearl” when sending the messages to Firms.</p> |
| 52 | SendingTime | Yes | <p>Time of message transmission expressed in UTC (Universal Time Coordinated), also known as GMT.</p> <p>This value must be within 60 seconds of the current time; else the order will be rejected.</p> <p>Format: YYYYMMDD–HH:MM:SS.uuu</p> |
| 56 | TargetCompID | Yes | <p>Identifies the party receiving the message.</p> <p>Firms should use the value “Pearl.”</p> <p>Pearl will use the Firm’s Line ID when sending the messages to Firms.</p> |

| Tag | FIX Name | Req'd | Details |
|-----|------------------|-------|--|
| 57 | TargetSubID | Cond. | <p>Sub identifier of the party receiving the message.</p> <p>Required for application messages delivered to the firms from Pearl.</p> <p>See Configuration section (1.4 Configuration) for more detail.</p> |
| 97 | PossResend | No | <p>Ignored in messages sent to Pearl.</p> <p>Set to Y in messages from Pearl during certain failure/recovery scenarios.</p> |
| 115 | OnBehalfOfCompID | Cond. | <p>Only applicable to messages sent to Pearl:</p> <p>Identifies the end client that is the originator of the message.</p> <p>This will be returned in the DeliverToCompID of messages corresponding to this message.</p> |
| 116 | OnBehalfOfSubID | Cond. | <p>Only applicable to messages sent to Pearl:</p> <p>Sub identifier of the end client.</p> <p>This will be returned in the DeliverToSubID of messages corresponding to this message.</p> |
| 122 | OrigSendingTime | Cond. | <p>Required for resent messages. If no data is available, this value is set to the SendingTime value.</p> <p>Format: YYYYMMDD-HH:MM:SS.uuu</p> |
| 128 | DeliverToCompID | Cond. | <p>Only applicable to messages sent from Pearl:</p> <p>Pearl will reflect back the data sent in OnBehalfOfCompID field.</p> |
| 129 | DeliverToSubID | Cond. | <p>Only applicable to messages sent from Pearl:</p> <p>Pearl will reflect back the data sent in OnBehalfOfSubID field.</p> |

2.2 Standard Message Trailer

The Standard Trailer terminates each administrative or application message in the FIX protocol. The trailer is used to segregate messages and contains the three-digit character representation of the Check Sum value. Tag must be present even for Firms that have disabled Check Sum validation.

The following table contains the Standard Trailer tags processed by Pearl. Any other Trailer tag will be ignored.

| Tag | FIX Name | Req'd | Details |
|-----|----------|-------|---|
| 10 | Checksum | Yes | Always the last field of a FIX message. |

3. Session Protocol

Please refer to **FIX v4.2 Protocol** document (<http://fixprotocol.org/specifications>) for details about **FIX session protocol**. This protocol layer offers session management capabilities such as establishing a FIX session, authentication, application/administrative messaging over TCP/IP, sequencing of messages, heartbeats and gap fills.

Order sending firm will always be the Initiator of the FIX session and Pearl is the *Acceptor*.

4. Administrative Messages

This section consists of administrative messages such as those that are used for session protocol.

4.1 Logon Request (MsgType = A)

Please refer to FIX v4.2 Protocol document for details about FIX Logon Request.

The logon message authenticates a user establishing a connection to a remote system. The logon message must be the first message sent by the Firm that needs to initiate a FIX session with the FIX Drop. Firms must wait for a Logon message as a response from the FIX Drop before sending other messages.

The message format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|------------|-------------------------|-------|---|
| | <i>Standard Header</i> | Yes | MsgType = A |
| 98 | EncryptMethod | Yes | (always unencrypted) |
| 108 | HeartBtInt | Yes | Value specified in seconds. Note: Must be > 0 and same value must be used by both sides. |
| 141 | ResetSeqNumFlag | No | Indicates both sides of a FIX session should reset sequence numbers |
| | <i>Standard Trailer</i> | Yes | |

Points to note:

- Firms can specify a heartbeat interval that is greater than zero and FIX Drop will use the same. Both sides must use that same interval to check if the other side is alive. A Heartbeat interval of 5 seconds is recommended. Upon missing of a single heartbeat, FOI will send a Test Request. Upon missing of 2 heartbeats, FIX Drop will send a logout and terminate the connection. Pearl recommends using as low of a value the reliability and latency of your telecommunications channel will allow.
- Encryption is not supported and hence the EncryptMethod field is ignored.
- When Firms reconnect due to a loss of connection, the login response from Pearl may contain a sequence number greater than what the firm expects. This will require the Firm to follow the FIX resend protocol to do a gap fill.

4.2 Heartbeat (MsgType = 0)

Please refer to FIX v4.2 Protocol document for details about FIX Heartbeat.

The heartbeat format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|------------|-------------------------|-------|--|
| | <i>Standard Header</i> | Yes | MsgType = 0 |
| 112 | TestReqID | Cond | Required when the heartbeat is the result of a Test Request message. |
| | <i>Standard Trailer</i> | Yes | |

Points to note:

- Check the Logon message for details about the heartbeat interval
- Each side must send a heartbeat only when the agreed upon interval has elapsed since the last message was sent.

4.3 Test Request (MsgType = 1)

Please refer to FIX v4.2 Protocol document for details about FIX Test Request.

The test request message forces a heartbeat from the opposing application. The test request message checks sequence numbers or verifies communication line status. The opposite application responds to the Test Request with a Heartbeat containing the TestReqID.

The heartbeat format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|------------|-------------------------|-------|-------------|
| | <i>Standard Header</i> | Yes | MsgType = 1 |
| 112 | TestReqID | Yes | |
| | <i>Standard Trailer</i> | Yes | |

Points to note:

- If heartbeat interval + 1 second has elapsed since the last message was received, a Test request can be issued. After two such iterations, the connection must be dropped. This ensures a proactive detection and cleanup of a broken TCP connection.

4.4 Resend Request (MsgType = 2)

Please refer to FIX v4.2 Protocol document for details about FIX Resend Request.

The message format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|---------|----------|-------|---------|
|---------|----------|-------|---------|

| | | | |
|-----------|-------------------------|-----|-------------|
| | <i>Standard Header</i> | Yes | MsgType = 2 |
| 7 | BeginSeqNo | Yes | |
| 16 | EndSeqNo | Yes | |
| | <i>Standard Trailer</i> | Yes | |

4.5 Reject – Session Level (MsgType = 3)

Please refer to **FIX v4.2 Protocol** document for details about **FIX Reject (session level)**.

FXD will disregard any message that is garbled, cannot be parsed or fails a data integrity check. Pearl will also terminate the connection.

The message format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|------------|-------------------------|-------|---|
| | <i>Standard Header</i> | Yes | MsgType = 3 |
| 45 | RefSeqNum | Yes | MsgSeqNum of rejected message |
| 371 | RefTagID | Cond | Required if reject reason refers to a specific tag |
| 372 | RefMsgType | Yes | The MsgType of the FIX message being referenced |
| 373 | SessionRejectReason | Yes | Code to identify reason for a session-level Reject message Valid Values: “0” = Invalid tag number “1” = Required tag missing “2” = Tag not defined for this message type “3” = Undefined tag “4” = Tag specified without a value “5” = Value is incorrect (out of range) for this tag “6” = Incorrect data format for value “7” = *Unused/Not applicable* “8” = *Unused/Not applicable* “9” = Comp ID problem “10” = SendingTime accuracy problem “11” = Invalid MsgType |
| 58 | Text | No | Will be supplied if there is a need to supply more information regarding the reject |
| | <i>Standard Trailer</i> | Yes | |

4.6 Sequence Reset (MsgType = 4)

Please refer to **FIX v4.2 Protocol** document for details about **FIX Sequence Reset (Gap Fill)**.

The message format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|------------|-------------------------|-------|-------------|
| | <i>Standard Header</i> | Yes | MsgType = 4 |
| 123 | GapFillFlag | No | |
| 36 | NewSeqNo | Yes | |
| | <i>Standard Trailer</i> | Yes | |

4.7 Logout Request (MsgType = 5)

Please refer to **FIX v4.2 Protocol** document for details about **FIX Logout Request**.

The logout message initiates or confirms the termination of a FIX session. Disconnection without the exchange of logout messages will be interpreted as an abnormal condition.

Before actually closing the session, the logout initiator must wait for the opposite side to respond with a confirming logout message. This gives the remote end a chance to perform any Gap Fill operations that may be necessary. The session may be terminated if the remote side does not respond in 5 minutes.

After sending the Logout message, the logout initiator should not send any messages unless requested to do so by the logout acceptor via a ResendRequest.

The message format is as follows:

| FIX Tag | FIX Name | Req'd | Details |
|-----------|-------------------------|-------|--|
| | <i>Standard Header</i> | Yes | MsgType = 5 |
| 58 | Text | N | Can be used to send readable information to the recipient. FOI will just log this and no alerts will be generated on any human readable display devices. |
| | <i>Standard Trailer</i> | Yes | |

5. Application Messages

This section consists of application messages.

5.1 Execution Report (MsgType = 8)

The Pearl FIX Drop Server transmits execution reports (MsgType = 8) back to the Firm. The execution report message is used to:

- Relay fill information on working orders
- Report post-trade fee calculations associated with a trade.

| FIX Tag | FIX Name | Req'd | Details |
|---------|------------------------|-------|--|
| | <i>Standard Header</i> | Yes | MsgType = 8 |
| 1 | Account | No | As specified on the order. Optional field. |
| 6 | AvgPx | Yes | Always filled with 0 (zero). |
| 11 | ClOrdID | Yes | Unique identifier of the order. This value uses the ID from the original order. Value must be 30 characters or less. |
| 14 | CumQty | Yes | Total number of filled options. Valid values: 0 – 999,999 |
| 17 | ExecID | Yes | Unique identifier for each Execution Report message. Uniqueness is guaranteed within a single trading day. |
| 18 | ExecInst | No | Instructions for order handling on exchange. Will be the same value as entered in the order (if used). Valid values: f = ISO |
| 20 | ExecTransType | Yes | Identifies the trade type. Valid values: 0 = New |
| 31 | LastPx | Yes | Price of the last fill. This field is not required for ExecTransType = 3 (Status). |

| FIX Tag | FIX Name | Req'd | Details |
|---------|-------------|-------|---|
| | | | (the number of decimal places might vary and is not limited to 3). |
| 32 | LastShares | Yes | Quantity of bought/sold contracts on the last fill. This field is not required for ExecTrans Type = 3 (Status). Valid values: 0 – 999,999 |
| 37 | OrderID | Yes | OrderID, as assigned by Pearl, is required to be unique for each chain of orders. |
| 38 | OrderQty | Yes | The number of contracts (total order quantity). |
| 39 | OrdStatus | Yes | Identifies the current status of an order. Valid values: 1 = Partially Filled 2 = Filled 6 = Pending Cancel |
| 40 | OrdType | Yes | Order type that is specified on the order. Valid values: 1 = Market 2 = Limit |
| 41 | OrigClOrdID | No | ClOrdID of the canceled or replaced order. This is the target order of the previous request and not the initial order of the day. |
| 44 | Price | Cond | Price for limit orders (OrdType = 2) Format follows Price field as described in MsgType D, G of the FOI specification. |
| 54 | Side | Yes | Side of order. Valid values: 1 = Buy 2 = Sell |
| 55 | Symbol | Yes | The 6 character OCC Security Symbol (class) for an option. |

| FIX Tag | FIX Name | Req'd | Details |
|---------|-------------------|-------|---|
| 58 | Text | Cond | User requested Cancel and Replace with ExecType equal to "6" or "E" contain partial Canceled Quantity Format: CxlQty:'value' Eg. CxlQty:40 Unsolicited Canceled (ExecType = 4) will contain a freeform human readable reason for the cancel. (See Error Code 0 in Appendix C) |
| 59 | TimeInForce | No | Specifies how long the order remains in effect. Valid values: 0 = DAY 1 = GTC (Good Till Canceled) 3 = IOC (Immediate or Cancel) |
| 60 | TransactTime | No | Time of execution/order creation expressed in UTC (Universal Time Coordinated), also known as GMT. Format: YYYYMMDD-HH:MM:SS.uuu |
| 77 | OpenClose | Cond | Specifies if this order opens a position or closes a position. Required except for Pearl member or Non-Member Market Maker orders Valid values: O = Open C = Close |
| 150 | ExecType | Yes | Identifies the type of execution report. Valid values: 1 = Partially filled 2 = Filled |
| 151 | LeavesQty | Yes | Number of open contracts for further execution. If the OrdStatus is Canceled or Rejected (no longer active) then LeavesQty = 0, otherwise LeavesQty = OrderQty - CumQty. |
| 167 | SecurityType | No | The type of security. Valid values: "OPT" |
| 200 | MaturityMonthYear | No | Expiration month and year, as specified on the order. |

| FIX Tag | FIX Name | Req'd | Details |
|---------|------------------|-------|--|
| | | | Format: YYYYMM (For example, 201009 is an expiration of September 2010.) |
| 201 | PutOrCall | No | As specified on the order. Valid values: 0 = Put 1 = Call |
| 202 | StrikePrice | No | Strike price for an option, as specified on the order. |
| 204 | CustomerOrFirm | No | Specifies the order origin type that is specified on the order. Valid values: 0 = Priority Customer 1 = Firm 2 = Broker/Dealer 4 = Market Maker 5 = Non-Member Market Maker 8 = Non-Priority Customer |
| 205 | MaturityDay | No | Expiration day of month, used in along with MaturityMonthYear (200) to fully specify the maturity date for options. Format: DD |
| 207 | SecurityExchange | Cond | Exchange ID (MIC code) of the Exchange on which this execution occurred when it occurs on an exchange other than Pearl. Example codes from http://www.iso10383.org/ Example Valid Values: "AMXO" = NYSE/AMEX Options "BATO" = BATS Options "XBOX" = BOX Options "C2OX" = C2 Options "XCBO" = CBOE Options "XISX" = ISE Options "GMNI" = ISE Gemini Options "MCRY" = ISE Mercury Options "ARCO" = NYSE/ARCA Options "XNDQ" = Nasdaq Options Market "XPHO" = Nasdaq OMX PHLX Options "XBXO" = Nasdaq BX |

| FIX Tag | FIX Name | Req'd | Details |
|---------|-----------------------------|-------|---|
| | | | “EDGO” = BATS EDGX Options “XMIO” = MIAX Options “EMLD” = MIAX Emerald Options “MXOP” = MEMX Options “SPHR” = MIAX Sapphire Options |
| 1003 | TradeID | Cond | The unique ID that identifies the trade at Pearl. Only available on Fill (ExecType 1 or 2) messages. |
| 9730 | AdditionalBillingParameters | Cond | For Order Executions (ExecType=1 or 2): A field containing additional (not contained elsewhere in Execution report or Order) parameters required for Pearl billing. See Appendix A: Additional Billing Parameters for details. For other Execution reports (ExecType is not 1 or 2): Tag will not be sent. |
| | <i>Standard Trailer</i> | Yes | |

5.2 Trade Cancel/Correct (MsgType = UCC)

The Pearl FIX Drop server transmits trade cancellations and corrections using this message format. This message is sent to relay information such as (but not limited to)

- A trade cancellation (bust)
- A price/size correction on a trade
- A clearing change correction on a trade. Clearing change includes
 - Trade split that results in one or more new trades, each of which will be transmitted using MsgType = UCC
 - Trade reassignment to another EEM MPID that may result in trade cancellation and new trade which will be transmitted using MsgType = UCC
 - Updates to clearing information, eg. Clearing MPID, CMTA, Account, Open/Close, Order Text, Origin

| FIX Tag | FIX Name | Req'd | Details |
|---------|------------------------|-------|---------------|
| | <i>Standard Header</i> | Yes | MsgType = UCC |

| FIX Tag | FIX Name | Req'd | Details |
|---------|----------------|-------|---|
| 20 | ExecTransType | Y | <p>0 = New Manual Trade (only due to clearing change)</p> <p>1 = Trade Cancel</p> <p>2 = Trade Correct</p> <p>Note: New Manual Trade and Trade Cancel messages can be generated due to a Clearing change correction. See CorrectionType field for details.</p> |
| 9020 | CorrectionType | Y | <p>1 = Not Applicable (Used when message is generated due to a trade cancel)</p> <p>2 = Price and/or Size change</p> <p>3 = This side Clearing change</p> <p>4 = Contra side Clearing change</p> <p>5 = Both side Clearing change</p> <p>Note: Clearing change includes trade split/reassignment that may result in New Manual Trade and Trade Cancel messages.</p> |
| 17 | ExecID | Y | It is always the ExecID in the original trade |
| 1003 | TradeID | Y | <p>Pearl assigned unique Trade ID for the day for a New Manual Trade created due to a clearing change</p> <p>When not a New Manual Trade, same as the Trade ID of the cancelled or corrected trade.</p> <p>Note: When TradeID is used in conjunction with CorrectionNum, Side and ExecTransType, this is a unique identifier for each corrected trade.</p> |
| 1126 | OrigTradeID | N | <p>TradeID of the trade being corrected.</p> <p>Note: When the message is for a New Manual Trade, this is TradeID of the trade that had the clearing change correction resulting in this New Manual Trade</p> |
| 9021 | CorrectionNum | Y | <p>Trade correction number.</p> <p>Used to identify version of the trade being corrected or canceled. Increments by 1 for each subsequent correction. New trades resulting from corrections may have a non-zero number.</p> |

| FIX Tag | FIX Name | Req'd | Details |
|---------|-------------------|-------|--|
| 37 | OrderID | Y | From original trade |
| 11 | ClOrdID | Y | From original trade |
| 42 | OrigTime | Y | GMT date-time of trade being corrected or cancelled |
| 60 | TransactTime | Y | GMT date-time of the cancel/correct trade |
| 167 | SecurityType | Y | The type of security. Valid values: "OPT" |
| 55 | Symbol | Y | From original trade |
| 200 | MaturityMonthYear | Y | From original trade |
| 205 | MaturityDay | Y | From original trade |
| 201 | PutOrCall | Y | From original trade |
| 202 | StrikePrice | Y | From original trade |
| 54 | Side | Y | From original trade |
| 31 | LastPX | Y | For Price/Size change, it is the latest price. Else, the value in the trade being corrected or cancelled |
| 32 | LastShares | Y | For Price/Size change and split trades, it is the latest size. Else, the value in the trade being corrected or cancelled |
| 77 | OpenClose | Y | If changed in correction, the latest corrected value. Else, the value supplied in the order |
| 109 | ClientID | Y | Clearing MPID. If changed in correction, the latest corrected value. Else, the value supplied in the order. If it is not provided in the order, it is the same as ExecutingMPID/TargetSubID. |
| 1 | Account | N | If changed in correction, the latest corrected value. Else, the value supplied in the order. |
| 439 | ClearingFirm | N | CMTA If changed in correction, the latest corrected value. Else, the value supplied in the order |

| FIX Tag | FIX Name | Req'd | Details |
|---------|-----------------------------|-------|--|
| 440 | ClearingAccount | N | If changed in correction, the latest corrected value. Else, the value supplied in the order |
| 58 | Text | N | If changed in correction, the latest corrected value. Else, the value supplied in the order |
| 9730 | AdditionalBillingParameters | N | Latest changes to additional billing parameters. Format is the same as tag 9730 reported in FOI/FXD execution report. See Appendix A for details on AdditionalBillingParameters. |
| | <i>Standard Trailer</i> | Yes | |

Points to note:

- Trade corrections or busts do not change the state or open contracts of orders
- Only Trade cancels and corrections of EEMs Orders are sent via this message
- Each correction will result in a Trade Cancel/Correct message (MsgType = UCC) to both the sides, if eligible based on MPID entitlement. In Clearing change update messages, contra side may see only an updated CorrectionNum
- **Important:** Pearl may choose to retransmit Trade Cancel/Correct messages in response to an interruption of the FIX Drop service. Pearl will coordinate with the firms before initiating these retransmissions. Firms can use a combination of TradeID, CorrectionNum, Side and ExecTransType as a unique key to know if a given message is a retransmitted message

6. Business Reject (MsgType = j)

Any business level message type from a firm will result in a business reject (j).

Note that if the message fails session level checks (e.g. incorrect body length, required tag missing, etc.), a session level reject (3) will be issued.

| FIX Tag | FIX Name | Req'd | Details |
|------------|-------------------------|-------|--|
| | <i>Standard Header</i> | Yes | MsgType = j |
| 45 | RefSeqNum | Yes | MsgSeqNum of rejected message |
| 372 | RefMsgType | Yes | MsgType of the FIX message being rejected |
| 379 | BusinessRejectRefID | Yes | RefID of the message being rejected. This is the ExecID in case an Execution report is being rejected and this is the ClOrdID in case an Order/Cancel message is being rejected. This will be the CrossID in case a New Order Cross is being rejected. |
| 380 | BusinessRejectReason | Yes | Code to identify reason for Business rejection. Valid values: 0 = Other 3 = Unsupported Message Type |
| 58 | Text | Cond | Required if BusinessRejectReason = 0 |
| | <i>Standard Trailer</i> | Yes | |

Appendix A: Additional Billing Parameters

Pearl will provide parameters used by Pearl for billing in tag 9730 of *execution report* message for all executions (trades). The following table gives the breakup of that field:

| Position | Number of Characters | Parameter Name | Description |
|----------|----------------------|----------------------|---|
| 1 | 1 | OrderOrigin | Origin (CustomerOrFirm) of the firm's side of the order |
| 2 | 1 | ContraOrigin | Origin (CustomerOrFirm) of the opposite side of this trade |
| 3 | 1 | ClassType | Indicates whether the underlying is being billed as maker/taker. 'M' = Maker/Taker ** (asterisk) = New value masked for backward compatibility. Upgrade to new version to see new values. |
| 4 | 1 | LiquidityIndicator | 'M' = Maker 'T' = Taker 'N' = Not Applicable ** (asterisk) = New value masked for backward compatibility. Upgrade to new version to see new values. |
| 5 | 1 | PbboMPV | 'P' = PennyAlways 'N' = Penny/Nickel 'D' = Nickel/Dime |
| 6 | 1 | MarketState | 'N' = Normal Trading 'O' = Opening ** (asterisk) = New value masked for backward compatibility. Upgrade to new version to see new values. |
| 7 | 1 | FreeTradingCondition | '1' = Regular , |

| Position | Number of Characters | Parameter Name | Description |
|----------|----------------------|-------------------|---|
| | | | '2' = ABBOUncrossed, ' ' = Not Applicable (space) '*' (asterisk) = New value masked for backward compatibility. Upgrade to new version to see new values. |
| 8 | 6 | RoutedOrderQty | Total Routed Away Quantity. Populated when the trade is executed at away exchange. Format: Fixed length integer prepended with zero I.E. 000012 |
| 14 | 1 | ContraTimeInForce | 0 = DAY 1 = GTC (Good Till Canceled) 3 = IOC (Immediate or Cancel) '*' (asterisk) = New value masked for backward compatibility. Upgrade to new version to see new values. |

Appendix B: Contact List

Please visit MIAX website at <http://www.MIAXGlobal.com> for obtaining most up-to-date contact list and other such information.

Appendix C: Revision History

| Revision Date | Version | Description |
|---------------|---------|---|
| Sep 30, 2016 | 1.0 | First Release |
| Oct 14, 2016 | 1.0a | Removed tag 442 (MultiLegReportingType) and tag 654 (LegRefID) from MsgType = UCC |
| Apr 24, 2018 | 1.1 | Message type= 8 – Added support for MIAX Emerald market |
| May 23, 2023 | 1.1b | SecurityExchange: Added 'MXOP' (MEMX Options) |
| Jul 25, 2023 | 1.1c | SecurityExchange: Added 'SPHR' (MIAX Sapphire Options) |

miax[®]

MIAXGlobal.com